

# BUCKMAN LABORATORIES, INC.

## MATERIAL SAFETY DATA SHEET



# KTND

Revision date: 7/19/2006

Phone 1-800-BUCKMAN

Buckman Laboratories, Inc.  
1256 North McLean Boulevard  
Memphis, TN 38108

**24 Hour Emergency Phone: (901) 767-2722**

### SECTION 1

### OSHA HAZARD CLASSIFICATIONS

Corrosive to eyes and skin. Sensitizer. Toxic by inhalation of mist.

### SECTION 2

### HAZARDOUS COMPONENTS

<u>Chemical Name</u>	<u>CAS Number</u>	<u>% by Weight</u>	<u>TLV</u>
Magnesium Nitrate	10377-60-3	1.7	Not available.

*Buckman Laboratories reports the component(s) listed above as known OSHA hazardous material(s) contained in this product.*

### SECTION 3

### FIRST AID INFORMATION

- Eye Exposure: Flush immediately with copious amounts of tap water or normal saline (minimum of 15 minutes). Take exposed individual to a health care professional, preferably an ophthalmologist, for further evaluation.
- Skin Exposure: Wash exposed area with plenty of water. Repeat washing. Remove contaminated clothing and wash thoroughly before reuse. If irritation persists consult a health care professional.
- Inhalation: If exposure by inhalation is suspected, immediately move exposed individual to fresh air. If individual experiences nausea, headache, dizziness, has difficulty in breathing or is cyanotic, seek a health care professional immediately.
- Ingestion: DO NOT INDUCE VOMITING. Rinse with copious amounts of water or milk, first. Irrigate the esophagus and dilute stomach contents by slowly giving one (1) to two (2) glasses of water or milk. Avoid giving alcohol or alcohol related products. In cases where the individual is semi-comatose, comatose or convulsing, DO NOT GIVE FLUIDS BY MOUTH. In case of intentional ingestion of the product seek medical assistance immediately; take individual to nearest medical facility.

## SECTION 4

**PRIMARY ROUTES OF EXPOSURE****1. Effects from Acute Exposure:**

**Eye Exposure:** Very hazardous in case of eye contact (irritant, corrosive). Inflammation of the eye is characterized by redness, watering, and itching.

**Skin Exposure:** Hazardous in case of skin contact (corrosive, irritant, sensitizer). Skin contact may produce burns. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.

**Inhalation:** May be harmful if inhaled. Do not breathe spray mists of the undiluted product. Effects will depend upon solution strength and length of time of exposure.

**Ingestion:** Ingestion is not expected to be a primary route of exposure.

**2. Effects from Chronic Exposure:**

The following information is based on tests with one or more of the active ingredients. In vitro mutagenicity studies reported both positive and negative results. Animal tests for birth defects were negative. Chronic dietary and drinking water studies did not reveal any adverse effects. Repeated exposure to skin may cause allergic reactions. This product has caused allergic reactions in animal studies and has been reported to cause allergic reactions in people.

## SECTION 5

**Toxicological Information****Acute Effects:**

Acute	Oral	(LD50) = 3810 mg/kg	Rat
Acute	Dermal	(LD50) = >5000 mg/kg	Rabbit
Acute	Inhalation	(LC50) = 1.4 mg/l ( 4 hours)	Female rat.
Acute	Inhalation	(LC50) = 1.5 mg/l ( 4 hours)	Male rat.

**Irritant / Sensitization Effects:**

Very hazardous in case of eye contact (irritant, corrosive). Inflammation of the eye is characterized by redness, watering, and itching.

Hazardous in case of skin contact (corrosive, irritant, sensitizer). Skin contact may produce burns. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.

May be harmful if inhaled. Do not breathe spray mists of the undiluted product. Effects will depend upon solution strength and length of time of exposure.

**Carcinogenic Potential:**

Not tested by Buckman Laboratories. Not shown as a carcinogen by OSHA, IARC, or NTP.

**Target Organs Effects:**

May cause damage to the following organs: upper respiratory tract, skin, eyes.

**Other Health Effects:**

The following information is based on tests with one or more of the active ingredients. In vitro mutagenicity studies reported both positive and negative results. Animal tests for birth defects were negative. Chronic dietary and drinking water studies did not reveal any adverse effects. Repeated exposure to skin may cause allergic reactions. This product has caused allergic reactions in animal studies and has been reported to cause allergic reactions in people.

**SECTION 6*****Environmental Toxicological Information***

LC50 = 0.16 mg/l 48 hours Daphnia magna  
 LC50 = 0.28 mg/l 96 hours Bluegill sunfish.  
 LC50 = 0.19 mg/l 96 hours Rainbow trout.  
 LC50 = 0.3 mg/l 96 hours Sheepshead minnow.  
 LC50 = 0.55 mg/l 96 hours Sand shrimp.  
 LC50 = 0.01 mg/l 96 hours Bay mussel.

**SECTION 7*****Physical and Chemical Properties***

**Appearance** ..... **Clear to light green. liquid**  
**Odor** ..... **Pungent. (Strong.)**  
**Density** ..... **1.02 to 1.04 (20°C / 68°F)**  
**Flash Point** ..... **Closed cup: >100°C (212°F). (Pensky-Martens.)**  
**Melting/Freezing Point** .... **-3°C (26.6°F)**  
**Boiling Point** ..... **100°C (212°F)**  
**Solubility** ..... **Soluble in cold water. Soluble in hot water.**  
**pH (Neat)** ..... **2.5 to 5 [Acidic.]**  
**pH (100 ppm in water)** ..... **6.5**  
**Vapor Pressure**..... **0.01 mm of Hg ( @ 20°C )**  
**o/w Partition Coefficient** ..... **Not available.**  
**Oxidizing/Reducing Properties** . **Not available.**  
**Viscosity** ..... **Dynamic: 3 cP**  
**Additional pH Information** ..... **Not available.**

**NOTE: The physical data presented above are typical values and should not be construed as specifications.**

**SECTION 8*****Fire and Explosion Information***

**Flammable Limits** ..... **Not available.**  
**Extinguishing Media** ..... **Water fog, carbon dioxide, foam, dry chemical.**  
**Special Firefighting Procedures** ..... **Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.**

**SECTION 9*****Reactivity Information***

**Stability** ..... **Stable under normal conditions of use and storage.**  
**Incompatibility** ..... **Strong acids, strong bases, strong oxidizers, reducing agents, amines, and mercaptans.**  
**Hazardous Decomposition Products** ..... **Thermal decomposition of product can produce toxic vapors of sulfur dioxide, hydrogen chloride, and oxides of nitrogen.**

**SECTION 10*****Handling Precautions***

Rubber gloves, safety glasses or goggles, body protective clothing and shoes are required. If splashing can occur, a face shield is advisable. Eye-wash fountains in the work place are recommended. Local exhaust should be maintained to control vapor and mist levels. Respiratory protection (organic vapor/acid gas respirator) is required for work areas where misting may occur. **DO NOT STORE IN DIRECT SUNLIGHT.** The handling precautions for this product are based on the characteristics of the neat product unless otherwise specified.

**SECTION 11*****Satisfactory Materials of Construction***

304 Stainless steel  
316 Stainless steel  
PVC - flexible  
PVC - rigid  
Polyethylene - crosslink  
Polyethylene - high density  
Polyethylene - low density  
Polypropylene  
Rehau Tubing  
EPDM rubber  
Butyl rubber  
ABS (Plastic)  
Teflon  
Tygon F-4040  
Tygon tubing R3603  
Polyurethane Tubing  
Pharmed Tubing  
FRP  
Norprene  
Dow Sillastic Tube  
Polycarbonate  
Polystyrene

**NOTE:** With respect to all other materials not listed above, user should be aware that use of such materials with this product may be hazardous and result in damages to such materials and other property and personal injuries. No data concerning such materials not listed above should be implied by the user.

**SECTION 12*****Spill, Leak, and Disposal Procedures*****SPILL AND LEAK RESPONSE GUIDELINES:**

**Important:** Before responding to a spill or leak of this product, review each section of this MSDS. Follow the recommendations given in the Handling Precautions sections. Check the Fire and Explosion Data section to determine if the use of non-sparking tools is merited. Insure that spilled or leaked product does not come into contact with materials listed as incompatible. If irritating fumes are present, consider evacuation of enclosed areas.

**Emergency Response Assistance:** Emergency technical assistance is available at any time from Buckman Laboratories, Inc., by calling (901) 767-2722.

Initially minimize area affected by the spill or leak. Block any potential routes to water systems (e.g., sewers, streams, lakes, etc.). Based on the product's toxicological and chemical properties, and on the size and location of the spill or leak, assess the impact on contaminated environments (e.g. water systems, ground, air equipment, etc.). There are no methods available to completely eliminate any toxicity this product may have on aquatic environments. Minimize adverse effects on these environments. Buckman Laboratories, Inc. can be contacted for technical assistance. Determine if federal, state, and/or local release notification is required (see Regulatory Classifications section of this MSDS). Recover as much of the pure product as possible into appropriate containers. Later, determine if this recovered product can be used for its intended purpose. Address clean-up of contaminated

environments. Spill or leak residuals may have to be collected and disposed of. Clay, soil, or commercially available absorbents may be used to recover any material that can not readily be recovered as pure product. Flushing residual material to an industrial sewer, if present at the site of a spill or leak incident, may be acceptable if authorized approval is obtained. If product and/or spill/leak residuals are flushed to an industrial sewer, insure that they do not come into contact with incompatible materials. Contact the person(s) responsible for the operation of your facility's industrial sewer system prior to intentionally flushing or pumping spills or leaks of this product to the industrial sewer.

#### DISPOSAL GUIDELINES

**Note:** Follow federal, state, and local regulations governing the disposal of waste materials.

**Neat Product:** Contact your Buckman representative or Buckman Laboratories, Inc., at (901) 278-0330.

**Contaminated Materials:** Determine if waste containing this product can be handled by available industrial effluent system or other on-site waste management unit. If off-site management is required, contact a company experienced in industrial waste management. This product is not specifically listed in 40 CFR 261 as a Resource Conservation and Recovery Act (RCRA) hazardous waste. However, spill or leak residuals may meet the criteria of a characteristic hazardous waste under this Act. Check the characteristics of the material to be disposed of and/or the physical and reactivity data given in this MSDS for the neat product.

**Container Disposal:** Empty containers, as defined by appropriate sections of the RCRA, are not RCRA hazardous wastes. However, insure proper management of any residuals remaining in container.

### SECTION 13

#### *Transportation and Shipping Information*

##### *DOT Shipping Information:*

**CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S., (5-Chloro-2-methyl-4-isothiazoline-3-one, 2-Methyl-4-isothiazolin-3-one), Class 8, UN3265, P.G. II, (ERG Guide 153)**

##### *IMO/IMDG Shipping Information:*

**CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S., (5-Chloro-2-methyl-4-isothiazoline-3-one, 2-Methyl-4-isothiazolin-3-one), Class 8, UN3265, P.G. II, MARINE POLLUTANT, (EmS No. F-A, S-B, ERG Guide 153, HazMat 4931466)**

##### *IATA Shipping Information:*

**CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S., (5-Chloro-2-methyl-4-isothiazoline-3-one, 2-Methyl-4-isothiazolin-3-one), Class 8, UN3265, P.G. II, (ERG Guide 153, ERG Code 8L)**

-----

**DOT "RQ": NONE**

*Unless otherwise stated, the shipping information provided above applies only to non-bulk containers of this product. Proper shipping name and general shipping information may vary depending on packaging and mode of shipment. All products shipped from Buckman locations have been properly packaged and labeled according to appropriate hazardous materials shipping regulations. If any alteration of packaging, product, or mode of transportation is further intended, different shipping information, including but not limited to proper shipping name, RQ designation, and labeling may apply. For further information pertaining to the shipping requirements for this product, contact Buckman's Transportation Department or DOT Coordinator.*

### SECTION 14

#### *Regulatory Information*

The following Regulations are known to apply to the use and disposal of this product. Additional Federal, State and Local regulations may also be applicable.

##### SARA (Superfund Amendments and Reauthorization Act)

*SARA 302 Extremely Hazardous Substances List ...*

**No components of this product are listed.**

*SARA 312 Hazard Category ...*

**Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard**

*SARA 313 Toxic Chemicals List ...*

This product contains the following toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372 :

**Magnesium Nitrate**

**CERCLA (Comprehensive Environmental Response, Compensation and Liability Act)**

No components of this product are present above the *de minimus* levels.

**RCRA (Resource Conservation and Recovery Act) Listed Hazardous Waste**

No components of this product are listed.

**CWA (Clean Water Act) Listed Substances**

No components of this product are listed.

**FDA ( Food and Drug Administration)**

This product is approved under the following FDA (21 CFR) sections : 175.105 - Limitation: For use only as an antimicrobial agent in polymer latex emulsions. / 175.300, 175.320 - Limitation: For use only as an antimicrobial agent in emulsion-based silicon coatings at a level not to exceed 50 mg active ingredient/Kg in the coating formulation. / 176.170, 176.180 - Limitations: For use only 1) as an antimicrobial agent for polymer latex emulsions in paper coatings at a level not to exceed 50 ppm active ingredient in the coating formulation and 2) as an antimicrobial agent for finished coatings and for additives used in the manufacture of paper and paperboard including fillers, binders, pigment slurries, and sizing solutions at a level not to exceed 25 ppm active ingredient in the coating formulations and additives. / 176.300 - Limitation: Not to exceed 2.5 pounds per ton of dry weight fiber..

**TSCA (Toxic Substances Control Act) Applicability**

All components are listed on the TSCA Inventory. Registered pesticides are exempt from the requirements of TSCA.

**FIFRA (Federal Insecticide, Fungicide, and Rodenticide Act)**

This product is a registered pesticide. EPA Reg. No. 1448-348

**HMIS/NPCA Rating ...** Health 3 Flammability 0 Reactivity 0

**NFPA Ratings .....** Health 3 Flammability 0 Reactivity 0

**State Regulations**

*Various State Right To Know Acts ...*

**Non-proprietary hazardous chemicals are listed in Section 2 of this MSDS. Should you require further information on specific proprietary or inert ingredients please contact Buckman Laboratories' Regulatory Affairs Department.**

The information on this Material Safety Data Sheet reflects the latest information and data that we have on hazards, properties, and handling of this product under the recommended conditions of use. Any use of this product or method of application which is not described in the Data Sheet is the responsibility of the user. This Material Data Safety Sheet was prepared to comply with the OSHA Hazard Communication regulations. While some components are claimed Trade Secret under OSHA Hazard Communication regulations, all known OSHA hazards associated with the Trade Secret component(s), if contained in this product, are fully disclosed.

Buckman Laboratories, Inc. warrants that this product conforms to its chemical description and is reasonably fit for the purpose referred to in the directions for use when used in accordance with the directions under normal conditions. Buyer assumes the risk of any use contrary to such directions.

Seller makes no other warranty or representation of any kind, express or implied, concerning the product, including **NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE**. No such warranties shall be implied by law and no agent of seller is authorized to alter this warranty in any way except in writing with a specific reference to this warranty.

The exclusive remedy against seller shall be in a claim for damages not to exceed the purchase price of the product, without regard to whether such a claim is based upon breach of warranty or tort.

Any controversy or claim arising out or relating to this contract, or breach thereof, shall be settle by arbitration in accordance with the commercial arbitration rules of the American Arbitration Association, and judgement upon the rendered by the Arbitrator(s) may be entered in any court having jurisdiction thereof.

